

Technical specifications for Metalcraft Personal Access Door

Standard Door size:

2045mm H x 875mm W for full frame door & 2035mm H x 875mm W for no bottom frame door

Special sizes available at additional cost

Door leaf

- 38mm sandwich panel consisting of two 0.59/G300 steel skins
- Laminated to a flame retardant EPS core
- Door leaf fitted with 3x 304 grade stainless steel hinge
- Proprietary T 6060 aluminium capped around the door panel
- Internal colour to match external colour

Door Frame

- Aluminium profile to suit clear opening of the entryway
- Aluminium profile powder coated to match
- Available in Outward opening frame or Inward opening frame
- Corner gussets for mitre reinforcing
- Stainless steel pan head screws for additional support at mitred section
- Santoprene rubber seal all around

Hardware

- Latch & latch Guard is fitted ex-factory
- Standard hardware is Legge G2 neptune lever type handle
- Optional non-standard hardware available at additional cost, including mortice locks, pinpad locks and panic bar locks

Finish

- Standard colours from NZ Steel
- Door supplied pre-hung
- Other colours at additional cost and availability

Packaging

- Comes in a heavy-duty timber crate
- Finished door weight – 28kgs
- Weight when packed – 44kgs

Optional Extras

- Holdback/doorstop
- Sill support bar & bottom threshold plates
- Kick plates & door closers
- Air vents/louvres
- Doors can be keyed alike
- Internal colour different to external colour
- Double doors

For technical advice please email Mohamed.adil@metpanels.co.nz or sales@metpanels.co.nz

Alternatively contact 09 277 8844 for assistance

For more info visit www.Metalcraftgroup.co.nz