

METALCRAFT INSULATED PANELS ASPIREPANEL

PURPOSE

Metalcraft Insulated Panels Limited supply Aspirepanel for use as insulated, fire-resistant, fully finished wall and roof panel.

EXPLANATION

Aspirepanels are lightweight, thermally efficient wall and roof panels manufactured in New Zealand. The panels have a polyisocyanurate (PIR) core sandwiched between 0.59 mm layers of galvanised steel and with a factory applied Colorsteel® finish. The Colorsteel® finish will depend on the specific exposure zone and use.

The panels are 1000 m in width, custom lengths and in the following thicknesses (mm): 50, 75, 100, 150. The thickness depends on the thickness of PIR core. The thickness determines thermal performance and span capability.

The panels are supplied with a tongue and groove joint and a lapped corrugation on both edges. The facings are available in the following profiles:

- Flat smooth profile
- Silkline
- Mesa
- Ribbed indented.

SCOPE AND LIMITATIONS OF USE

Scope	Limitations
Location	
In all wind zones up to and including extra high wind zone as defined in NZS 3604:2011 or a calculated wind design pressure (ULS) of 2.5 kPa.	➤ In accordance with Aspirepanel load span tables.
In all exposure zones as defined in NZS 3604:2011.	<ul style="list-style-type: none"> ➤ Where the system is to be used in a microclimate (as defined in clause 4.2.2, NZS 3604:2011), Metalcraft Insulated Panels is to be consulted. ➤ In exposure zone D, Colorsteel® Maxx® must be specified. ➤ In exposure zone C, Colorsteel® Maxx® or Endura® may be specified. ➤ In exposure zone B, any Colorsteel® product may be specified.
With a snow loading of up to 1 kPa.	
Greater than 1 m from a relevant boundary.	
Building	
In new buildings where the relevant part of the building complies with the NZ Building Code or in existing buildings where the designer and installer have assured themselves that the relevant part of the building is adequate for the intended building work.	
In all building uses.	<ul style="list-style-type: none"> ➤ Where material group 1S or greater is required. ➤ Where compliance with G3.3.2 (a, b) is required, Colorsteel® CP-Antibacterial must be specified for the internal facing of the panel.
As a wall panel.	<ul style="list-style-type: none"> ➤ Where the panels are to be load-bearing, they must be installed in conjunction with steel or timber structural framing and on a concrete slab or subfloor structure. ➤ With joinery that complies with NZS 4211:2008. ➤ In buildings that require fire-resistance rating (FRR) for passive fire protection, the passive fire protection systems must be specifically designed. ➤ With any building height up to a permissible wind design pressure of 2.5 kPa. ➤ Where the building has a building height greater than 10 m and upper floors contain sleeping uses or other property, then the external wall must be subject to specific fire engineering design in respect of vertical spread of flame.
As a roof panel.	➤ In accordance with Aspirepanel load span tables.

CONDITIONS

The specification and installation of Aspirepanel are to be in accordance with the ThermoPanel EPS specification and installation. This documentation is available from <https://www.metalcraftgroup.co.nz/products/metal-insulated-panels/products/thermopanel-eps/>.

ASPIREPANEL™

MADE IN NZ FOR LONGER LENGTHS AND QUICKER SUPPLY



For further assistance
please contact:

- ☎ +64 9 277 8844
- ✉ sales@metpanels.co.nz
- 🌐 www.metalcraftpanels.co.nz

USEFUL INFORMATION

For design, installation, maintenance and warranty information for Aspirepanel, and for supply and manufacturing information, and the statement made about s26 of the Building Act 2004, refer to www.metalcraftpanels.co.nz.

OTHER CERTIFICATIONS AND APPROVALS HELD BY THE STEEL MANUFACTURER:

As the manufacturer of the steel that is used in the manufacture of Aspirepanel, New Zealand Steel Ltd. provides assurance that the steel:

- has been manufactured in accordance with AS 1397-2001
- is coated in accordance with AS/NZS 2728:2013 or galvanized in accordance with AS/NZS 2312.2:2014.

New Zealand Steel Ltd. has established an Environmental Management System certified to ISO 14001. For more information on the specific exposure zones and environmental impacts of the product, refer to www.colorsteel.co.nz.

PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all Metalcraft Insulated Panels requirements, Aspirepanel will comply with or contribute to compliance with the following performance claims:

NZ Building Code clauses		BASIS OF COMPLIANCE	
Compliance statement	Demonstrated by		
B1 Structure B1.3.1, B1.3.2, B1.3.3 (a, b, e, f, h, j), B1.3.4 (b, c, d e)	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause B1. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	➤ Span in accordance with Aspirepanel load span tables.
B2 Durability B2.3.1(a)	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause B2. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	
C3 Fire affecting areas beyond the fire source C3.4 (a)	ACCEPTABLE SOLUTION C/AS2 1st Edition June 2019	➤ The panel achieves a material group 1S when tested to ISO 9705:1993. The test was carried out by BRANZ and BRANZ is accredited to carry out this test (BRANZ, 6/05/2021).	
E2 External moisture E2.3.1, E2.3.2, E2.3.3, E2.3.7 (b, c)	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause E2. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	
E3 Internal moisture E3.3.1, E3.3.4, E3.3.5, E3.3.6	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause E3. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	
F2 Hazardous building materials F2.3.1	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause F2. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	
G3 Food preparation and prevention of contamination G3.3.2 (a, b)	ALTERNATIVE SOLUTION	➤ Product is comparable to ThermoPanel EPS with respect to compliance with Clause G3. Compliance of ThermoPanel based on GlobalMark CodeMark certification evaluation (GlobalMark, 28/06/2017).	
H1 Energy Efficiency H1.3.1 (a, b), H1.3.2E	ALTERNATIVE SOLUTION	➤ Determination of R-values and energy performance of PIR [DASCO, 30/08/2019].	
Other performance statement		BASIS OF STATEMENT	
Performance statement	Demonstrated by		
Aspirepanel will not contaminate potable water.	AS/NZS 4020:2005.	➤ Claimed by New Zealand Steel Ltd. [New Zealand Steel Ltd. 2018].	➤ BRANZ statement that metal roof is suitable [BRANZ, 2018].

SOURCES OF INFORMATION

- BRANZ. [6/05/2021]. *FI13647-001-C1 Group Number Classification*.
- BRANZ. *Water. Harvesting rainwater*. Retrieved from <http://www.level.org.nz/water/water-supply/mains-or-rainwater/harvesting-rainwater/>. [Accessed on 25/06/2020].
- DASCO. [30/08/2019] *Product Test Report. R-Value (m2.K/W). Test method: KS M 3809*. Report No. DA-190830-22-01.
- Global-Mark. [28 June 2017] *Metalcraft Insulated Panel System CodeMark Certificate of Conformity*. Certificate No. GM-CM30078-RevC. Retrieved from <https://www.building.govt.nz/assets/Uploads/building-code-compliance/certifications-programmes/product-certification-scheme/product-certificate-register/metalcraft-insulated-panel-system.pdf>. [Accessed on 18/06/2020].
- red co Consulting Professional Engineers. [n.d.] *Metalcraft suPIRspan – Load-span Curves*.
- New Zealand Steel Ltd. [October 2018] *Product technical statement v2018.1*. Retrieved from <https://tinyurl.com/y7hldxx6>. [Accessed on 18/06/2020].
- New Zealand Steel Ltd. [October 2018] *Environmental Categories, Warranty & Product Maintenance Recommendations*. Retrieved from <https://tinyurl.com/y9paxqag>. [Accessed on 18/06/2020].
- New Zealand Steel Ltd. [October 2018] *Incompatible Materials*. Retrieved from <https://tinyurl.com/ybspk5y6>. [Accessed on 18/06/2020].

- Where a standard is referenced it is to be read as amended by the acceptable solution or verification method as applicable.
- Sources of information also include the Building Act 2004 and its regulations, including the Building Code (Schedule 1 of the Building Regulations 1992), Acceptable Solutions and Verification Methods, and relevant cited standards.
- The quality and assurance that the supplied products meet the performance claims stated in this pass™ are the responsibility of the company that is the holder of this pass™.
- The availability of the information about the supplied products required to be disclosed under s14G(3) is the responsibility of the company that is the holder of this pass™.

Metalcraft Insulated Panels confirms that if Aspirepanel is used in accordance with the requirements of this pass™ the product will comply with the NZ Building Code and other performance claims set out in this pass™ and the company has met all of its obligations under s14G(2) of the Building Act.

Date of first issue: 04/04/2021

Date of current issue: 19/07/2023

NZBN: 9429036310852

Scan or click this QR code for a full download of Compliance Documentation for this pass™.
www.metalcraftgroup.co.nz



Kevin Brunton

Kevin Brunton, Technical Director, TBB confirms that the process used to prepare this pass™ on behalf of Metalcraft Insulated Panels has been undertaken in accordance with MBIE PTS guidelines and in accordance with the TBB pass™ process which is within the scope of TBB's ISO 9001 certification.

9606D66ADE51EA6CCC25850D00239F99

139 Roscommon Road, Wiri, Auckland > sales@metpanels.co.nz > 64 9 277 8844 > www.metalcraftpanels.co.nz

Copyright © 2017, The Building Business Limited (TBB). All rights reserved.

VERSION: 2.5