

Technical specifications for Metalcraft Double Door

Door size:

We do not have a standard size for double doors and will need to be given a size.

Please follow the instructions on the PA Double Door Order Form.

Door leaf

- 38mm sandwich panel consisting of two 0.59/G300 steel skins
- Laminated to a flame-retardant EPS core
- Door leaf fitted with 3x 304 grade stainless steel hinge
- Proprietary T 6060 aluminium capped around the door panel
- Internal colour to match external colour

Door Frame

- Aluminium profile to suit clear opening of the entryway
- Aluminium profile powder coated to match
- Available in Outward opening frame or Inward opening frame
- Corner gussets for mitre reinforcing
- Stainless steel pan head screws for additional support at mitred section
- Santoprene rubber seal all around

Hardware

- Latch & latch Guard is fitted ex-factory
- Standard hardware is Legge G2 Neptune lever type handle
- Optional non-standard hardware available at additional cost, including mortice locks, pinpad locks and panic bar locks
- Flush Bolt

Finish

- Standard colours from NZ Steel
- Door supplied pre-hung
- Other colours at additional cost and availability

Packaging

- Comes in a heavy-duty timber crate
- Finished door weight – 95kgs
- Weight when packed – 130kgs

Optional Extras

- Holdback/doorstop
- Sill support bar & bottom threshold plates
- Kick plates & door closers
- Doors can be keyed alike